



PUMPING STATION DIMENSIONS		ACCESSORIES AND OPTIONS SPECIFICATIONS		NOTES
ITEM	DATA	REMARKS	PART	SPECIFICATIONS
A			PUMP	
B			MAKE	
C			MODEL	
D			HORSEPOWER	
E			VOLTAGE	
F			PHASE	
G			GPM	
H			TDH	
I			RPM	
J			CONTROL PANEL	NEMA
K			VOLTAGE	HZ
L			COVERS	CYCLES
M			W WELL	VOLTS
N			V VAULT	
O			VALVES	
P			PLUG/GATE CHECK	
Q			EXTENDED BASE	
R			WINCH	
S			VENTS	
T			W WELL	
U			V VAULT	
V				
W				
X				
Y				
Z				

- 1) JOINT SEAL BETWEEN PRECAST MANHOLE SECTIONS ON SEWERS SHALL BE RESILIENT AND FLEXIBLE GASKET JOINTS PER ASTM C443 OR LATEST EDITION
- 2) PRECAST MANHOLES SHALL CONFORM TO THE REQUIREMENTS OF ASTM C478 AND SHALL BE CLASS III
- 3) BASE OF WET WELL CONSISTS OF 4000 PSI CONCRETE



McLAUGHLIN & ASSOCIATES COMPANY, Inc.
 1259 Smith Court
 Rocky River, OH 44116
 Phone (440)333-3730
 Fax 333-8778